

**Material**

Reinforced PVC

Colour

White / other colours to order

Length

15, 25, 50m standard, other lengths available on order up to 100m

Temperature Resistance

- 0° up to + 50° C

Applications

Forced ventilation in mining and tunnelling

Available variants

Comes with suspension strip, hooks and wires available with cuff couplings or end rings

Properties

- antistatic
- light weight
- flame retardant
- rot resistant

EximoTempVent

TempVent LayFlat

Antistatic, flame retardant, layflat ducting

Technical Data

Further diameters available upon request.
Technical data are based on +20 °C.

PRODUCT CODE	Max work Pressure bar
TEMPFLAT305CB10	0.350
TEMPFLAT305CB5	0.350
TEMPFLAT305EB10	0.350
TEMPFLAT305EB5	0.350
TEMPFLAT456CB10	0.225
TEMPFLAT456CB5	0.225
TEMPFLAT456EB10	0.225
TEMPFLAT456EB5	0.225
TEMPFLAT508CB10	0.200
TEMPFLAT508CB5	0.200
TEMPFLAT508EB10	0.200
TEMPFLAT508EB5	0.200

Antistatic

PRODUCT CODE	Max work Pressure bar
TEMPFLAT305CB10	0.350
TEMPFLAT305CB5	0.350
TEMPFLAT305EB10	0.350
TEMPFLAT305EB5	0.350
TEMPFLAT456CB10	0.225
TEMPFLAT456CB5	0.225
TEMPFLAT456EB10	0.225
TEMPFLAT456EB5	0.225
TEMPFLAT508CB10	0.200
TEMPFLAT508CB5	0.200
TEMPFLAT508EB10	0.200
TEMPFLAT508EB5	0.200